

# **TELEDYNE ANALYTICAL INSTRUMENTS**

## **MODEL 9060** **Zirconium Oxide Flue Gas Oxygen Analyzer**



Optimizing combustion efficiency and minimizing exhaust emissions are important for proper operation of nearly every industrial process that burns fuel. From clean burning natural gas to dirty coal fired kilns, Teledyne's Model 9060 provides reliable and efficient O<sub>2</sub> monitoring capabilities by combining field proven zirconium oxide sensor technology with a powerful and versatile microprocessor based controller.

### **Model 9060 Control Unit**

The 9060 O<sub>2</sub> analyzer / transmitter provides in-situ analysis capability which can accept signals from up to two zirconia probes for averaging or backup purposes in furnaces, kilns, and boilers with sample temperatures ranging from ambient up to 1400° C. This unit is provided within a compact, steel, NEMA-4, easily installed, gasketed enclosure suitable for wall mounting. Purged or explosion proof design enclosures rated for hazardous areas can also be supplied.

### **Easy Set Up**

Analyzer functions and adjustments are easily accessed via a 7 key membrane keyboard. By using the prompting keys and following the display codes from the 2 line alphanumeric LCD screen, the user can easily interface with and set up the 9060 for field operation.

### **Easy Calibration / Self Diagnostic Features**

The 9060 provides standard programmable automatic calibration and auto-purge outputs. The user can program the cal/purge sequence to an alarm relay for external indication. The 9060 has also been designed with a probe diagnostic loop to continuously monitor for probe impedance to ensure the sensor is functioning properly. The electronics self-calibrates all inputs every minute.

### **Easy Interface**

The 9060 provides two isolated 4-20mADC linearized control signal outputs. One is dedicated to the O<sub>2</sub> signal and the other is user selectable from thirteen other variables. In addition, an RS-232 / RS-485 printer / computer interface capability is provided. One general diagnostic alarm and three field selectable alarms with switching are provided standard.

### **Additional Features**

An integral automatic reference pump is provided as standard. This pump draws atmospheric air and delivers it to the zirconium sensor as reference air in lieu of customer supplied instrument air. If the operator desires, the pump can be bypassed and instrument air, at a flow of 50 cc/min, can be delivered to the sensor as required.

### **Applications**

- Gas, oil, pulverized coal and black liquor boilers
- Cement, lime and ceramic kilns
- Refinery process heaters and furnaces
- Blast furnace ovens
- Soaking pit and heat treating furnaces
- Thermal cracking furnaces
- Catalyst regeneration
- Asphalt processes
- Utility boilers

**Built for Reliability and Performance**

# Model 9060 Specifications

**Range of Output 1:** Field selectable linear from 0-1% to 0-100% O<sub>2</sub>

**Output 2:** Can be applied to the optional second sensor input or to one of the following selectable variables:

Combustibles	O <sub>2</sub> deficiency	Probe EMF
Carbon dioxide	Efficiency	Stack temperature

**Display Choice:**

O <sub>2</sub> deficiency	Probe EMF	Combustibles
Carbon dioxide*	Efficiency*	Stack temperature
Probe temperature	Sensor impedance	
Ambient temperature	Run hours and date since last service	

\*Calculated values

**Accuracy and Repeatability:** ±1% of actual measured oxygen value with a repeatability of ±0.5% of measured value

**Response time:** 90% in less than 4 seconds - typical

- Inputs:**
- One or two zirconia oxygen probes or sensors
  - Stack or spare thermocouple, type T, J, K, R, S, or N
  - Main flame safety interlock (for heated probes only)
  - Purge pressure switch
  - Dual fuel selector
  - Remote alarm acknowledge

**Outputs:** Two linearized isolated 4-20mA DC signals

**Max. load impedance:** 4-20 mA isolated output 600 ohms

**Alarms:** Common alarm relay with 20 alarm functions and three programmable alarm relays for low, very low and high O<sub>2</sub>, probe temp. low, calibration error, pump failure and horn

**Computer / Printer communications:** RS-232 or RS-485 for connection of a computer terminal or printer for diagnostics of the analyzer, probe, sensor or combustion appliance

**Purge and Calibration check:** One purge and two calibration check output relays to operate, solenoid valves

**Reference gas pump:** Integral diaphragm pump delivers atmospheric air to the ZrO<sub>2</sub> sensor, or customer can supply their own instrument air (50 cc/min) for reference purposes

**Relay contacts:** 0.5A-24 VAC, 1A-30 VDC, 50 VAC, or 30 VDC max

**Ambient temperature:** 32-122°F (0-50°C)

**Connection cable:** Special cable containing shield, thermocouple compensating lead, sensor conductors and heater conductors where a heated probe or sensor is used (optional)

**Power requirements:** 120 or 240 VAC, 50/60 Hz, 125 VA (heated probe or sensor), 5 VA (unheated probe)

**Max. power consumption:** Unheated probe at 110 VAC, 70mA; Heated probe at 110 VAC, 1.0 mA; Unheated probe at 240 VAC, 40mA; Heated probe at 240 VAC, 2.0 mA

**Weight:** 5.5 lbs

**Enclosure:** NEMA-4, suitable for outdoors, wall or surface mounting

**Dimensions:** 10.2" W x 5.1" H x 3.7" D

**Accessories:** In-situ probes and sampling sensors Class I, Div 1, Group B, C, D enclosures for hazardous areas

- Probe and sensor cables
- Sample aspirator (for extractive probe)
- Purge and calibration check gas solenoid valves
- Calibration check flowmeters

## Series 9060 Zirconium Oxide Sensors / Probes

<b>9060H</b>	Heated probe design for typical stack gas applications
<b>9060UH-LT</b>	Unheated probe design (with 253MA sheath)
<b>9060UH-HT</b>	Unheated probe design (with alumina ceramic sheath) – suited for high temp applications
<b>9060UH-C</b>	Unheated probe design (with proprietary sheath for corrosion resistance) -- suited for corrosive / acid gas content applications.
<b>9060H-EX</b>	Heated probe design for extractive applications

## TELEDYNE ANALYTICAL INSTRUMENTS

A Teledyne Technologies Company  
16830 Chestnut Street  
City of Industry, California 91748, USA

TEL: 626-934-1500 FAX: 626-934-1651  
TOLL FREE: 888-789-8168

Visit Our Web Site at:  
[www.teledyne-ai.com](http://www.teledyne-ai.com)

## Warranty

Instrument is warranted for 1 year against defects in material or workmanship

NOTE: Specifications and features will vary with application. The above are established and validated during design, but are not to be construed as test criteria for every product. All specifications and features are subject to change without notice.

